# MATERIAL SAFETY DATA SHEET

### **SECTION 1 - IDENTIFICATION**

Product identifier : FYFANON ULV AG

Product Code(s) None reported.

**Product Use** Active ingredient in insecticides.

**Chemical Family** Mixture

Supplier's name and address: Manufacturer's name and address:

Cheminova, Inc. Cheminova A/S

One Park Drive, Suite 150 PO Box 9 PO Box 110566 DK-7620 Lemvig, , Denmark

Research Triangle Park, NC, USA

27709

: 919-474-6600 (8:00 AM - 5:00 PM, EST, Monday-Friday)

Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 24 Hr. Emergency Tel#

(Outside U.S.).

For Medical Emergencies: (800) 303-6950

EPA Reg. No. 67760-35

Information Telephone #

# SECTION 2 - HAZARDS IDENTIFICATION

: OSHA: This material is classified as hazardous under OSHA regulations (29CFR Classification

1910.1200). Hazardous classification: Unstable (reactive); Acute Health Hazard;

Chronic Health Hazard.

WHMIS information: This product is a Pest Control Product and is not regulated as a Controlled Product under the Hazardous Products Act (HPA). For informational purposes, this product would have the following WHMIS classification: Class D2B (Materials Causing Other Toxic Effects, Toxic Material); Class F (Dangerously

Reactive Material).

Colourless to light yellow liquid. Slightly aromatic odour. **Emergency Overview** 

Warning! Dangerous exothermic decomposition may occur at temperatures greater than 212°F / 100°C. May be harmful if inhaled or swallowed. May cause eye irritation. Contains material which can cause nervous system damage. May be dangerous for the environment. Malathion is toxic to birds, fish, aquatic invertebtates, aquatic life stages of amphibians and highly toxic to

#### **POTENTIAL HEALTH EFFECTS:**

# Signs and symptoms of short-term (acute) exposure

Inhalation: Fyfanon (Malathion) is a cholinesterase inhibitor of low mammalian toxicity. However storage at

too high temperatures may induce formation of the much more toxic and synergistic contaminant isomalathion (LD50 acute oral, rat = 89 mg/kg). Malathion and isomalathion can affect you when breathed in and can cause organophosphorous poisoning. Symptoms of poisoning may include headache, nausea, vomiting, blurred vision, tightness in chest, drooling, frothing of mouth and nose,

convulsions, coma and death.

Skin : Direct skin contact may result in little or no irritation. Malathion and isomalathion can be rapidly

absorbed through all skin surfaces. Causes symptoms similar to those listed for inhalation.

Direct contact causes eye irritation. Malathion and isomalathion can be rapidly absorbed through all

skin and eye surfaces. Causes symptoms similar to those listed for inhalation.

Malathion and isomalathion are poisons through ingestion. Causes symptoms similar to those listed Ingestion

for inhalation.

## Effects of long-term (chronic) exposure

Prolonged or repeated overexposure may cause behavioral changes.

Carcinogenic status See TOXICOLOGICAL INFORMATION, Section 11.

Cholinesterase inhibitor. See TOXICOLOGICAL INFORMATION, Section 11. Additional health hazards

Potential environmental effects

Eyes

: Malathion is toxic to birds, fish, aquatic invertebtates, aquatic life stages of amphibians

and highly toxic to bees. See ECOLOGICAL INFORMATION (Section 12).

# SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	CAS#	Wt.%
Malathion	121-75-5	60.00 - 100.00

### SECTION 4 - FIRST AID MEASURES

Inhalation : Immediately remove person to fresh air. If breathing has stopped, give artificial

respiration. Seek immediate medical attention/advice.

Skin contact : Immediately flush skin with running water for at least 15 minutes, while removing

contaminated clothing. If irritation persists, seek prompt medical attention. Wash

contaminated clothing before re-use.

Eye contact : Flush eyes thoroughly with running water for at least 20 minutes, holding eyelids open

to ensure complete flushing. Seek immediate medical attention/advice.

Ingestion : Do NOT induce vomiting. Have victim rinse mouth with water, then give one to two

glasses of water to drink. Induce vomiting ONLY under the direct supervision of qualified medical personnel or a poison control centre. Never give anything by mouth

to an unconscious person. Seek immediate medical attention/advice.

Notes For Physician : Malathion is a cholinesterase inhibitor affecting the central and peripheral nervous

systems and producing respiratory and cardiac depression. Decontamination procedures such as whole body washing, gastric lavage and administration of activated charcoal are often required. If symptoms are present, administer atropine sulphate in large doses. Two to four mg intravenously or intramuscularly as soon as possible. Repeat at 5 to 10 minute intervals until signs of atropinization appear and maintain full atropinization until all organophosphorous is metabolised. Obidoxime chloride (Toxogonin), alternatively pralidoxime chloride (2-PAM), is a pharmacological antidote and may be administered as an adjunct to, but not a substitute for atropine, which is a symptomatic and often life-saving antidote. At first sign of pulmonary edema, the patient should be given supplemental oxygen and treated symptomatically. Continued absorption of Malathion may occur and relapse may occur after initial improvement. VERY CLOSE SUPERVISION OF THE PATIENT IS INDICATED FOR

AT LEAST 48 HOURS.

# **SECTION 5 - FIRE FIGHTING MEASURES**

#### Fire hazards/conditions of flammability

: This product is considered non-flammable. Material will decompose rapidly when exposed to heat (>212oF / 100oC) and flame, increasing the risk of explosion. Heat of decomposition may cause closed containers to build up pressure and explode.

Flammability classification (OSHA 29 CFR 1910.1200)

: Non-flammable.

Oxidizing properties : None known.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Suitable extinguishing media : Carbon dioxide or dry chemical for small fires. For large fires, use water spray or

foam

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Avoid spreading burning liquid with water spray used for cooling purposes.

Hazardous combustion products

Carbon oxides; Oxides of phosphorus; oxides of sulphur; dimethyl sulfide; irritating

fumes and smoke.

NFPA Rating 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

: Health: 1 Flammability: 1 Instability: 1 Special Hazards: None

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

Page 3 of 7

MSDS Revision Date (dd/mm/yyyy): 16/03/2010

Personal precautions

: Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

**Environmental precautions** 

Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply. Do not flush into surface water or sanitary sewer system. Uncontrolled discharge into water courses must be alerted to the appropriate regulatory body.

Spill response/cleanup

: Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Contain and absorb spilled material with inert, non-combustible absorbent material, such as sand. Sweep up and shovel into suitable containers for disposal. Notify the appropriate authorities as required. Carefully cover spilled material with soda ash or quicklime to neutralize. Do not flush into surface water or sanitary sewer system. For large spills on surfaces other than pavement (e.g. soil or sand), spills may be handled by digging up and removing the affected surface and placing it in approved containers.

Spills in water should be contained as much as possible by isolation of the contaminated water. The contaminated water must be collected and removed for treatment or disposal. Uncontrolled discharge into water courses must be alerted to the appropriate regulatory body. The used containers should be properly closed and labelled. Notify the appropriate authorities as required.

**Prohibited materials** 

: None known.

Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).

US CERCLA Reportable quantity (RQ): Malathion (100 lbs / 45.4 kg)

### SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures

: This material is a toxic liquid. Wear chemically resistant protective equipment during handling. Use only in well-ventilated areas. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Do not use near welding operations, flames or hot surfaces. Malathion should never be heated above 1310F / 550C and also local heating above this temperature should be avoided. Keep away from acids and other incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling. Use caution when opening cap.

Storage requirements

Store in a cool, dry, well ventilated area. Keep away from incompatibles. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area. Inspect periodically for damage or leaks. Product should be stored at temperatures not exceeding 68 to 77oF (20 to 25oC). Protect against physical damage.

Incompatible materials

 Strong alkalies, amines and strong oxidizing compounds. The product can corrode iron, steel, tin plate and copper. Fyfanon is rapidly hydrolysed at pH > 7.0.

Special packaging materials

Always keep in containers made of the same materials as the supply container.

### SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits									
	ACGIH TLV		OSHA PEL						
<u>Ingredients</u>	<u>TWA</u>	STEL	PEL	<u>STEL</u>					
Malathion	1 mg/m³ (inhalable)	N/Av	15 mg/m³ (total dust)	N/Av					

### Ventilation and engineering measures

: Provide sufficient ventilation to keep vapour concentration below the given TLV and/or

Respiratory protection

: Respiratory protection is required if the concentrations exceed the TLV. Wear a pesticide respirator jointly approved by the MSHA and NIOSH. Seek advice from respiratory protection specialists.

Skin protection

: Wear impervious gloves, such as barrier laminate, butyl rubber, nitrile rubber or viton. Advice should be sought from glove suppliers.

MSDS Revision Date (dd/mm/yyyy): 16/03/2010 Page 4 of 7

Eye / face protection : Safety glasses with side-shields or chemical splash goggles.

Other protective equipment : Wear appropriate protective clothing to prevent skin contact, such as coveralls or long

sleeved shirt, long pants, and shoes and socks. Other protective equipment, such as an eyewash station and safety shower, may be required depending on exposure and

on workplace standards.

General hygiene considerations

Avoid contact with skin, eyes and clothing. Remove soiled clothing and wash it thoroughly before reuse. Separate contaminated work clothes from street clothes. Always wash hands, face and arms with soap and water before smoking, eating or drinking. After work, take off all protective equipment, work clothes and shoes, and wash with soap and water. Respirator should be cleaned and filter replaced according to manufacturer's instructions. Wear only clean, uncontaminated clothes when leaving place of work. Persons working with this product for a longer period should have frequent blood tests for cholinesterase levels. If the cholinesterase levels fall below a critical point, no further exposure should be allowed until it has been determined, by means of blood tests, that cholinesterase levels have returned to normal.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid Appearance : Colourless to light yellow

liquid.

Odour : Slightly aromatic odour. Odour threshold : N/Av

**pH** : 3.7 - 3.8 (equal

amounts of Fyfanon and distilled water)

**Boiling point** : 313 - 315°F / 156 - **Specific gravity** : 1.23 g/mL @ 20°C

157°C

Melting/Freezing point : 37.1°F / 2.85°C Coefficient of water/oil distribution

: Kow = 560

: 148.2 mg/L @ 25°C

Vapour pressure (mmHg @ 20° C / 68° F)

: 3.4 x 10 -6 mmHg @

25°C;

1.4 x 10 -4 mmHg @

45°C

Vapour density (Air = 1) : N/Av Evaporation rate (n-Butyl acetate = 1)

: N/Av

Volatile organic Compounds (VOC's)

Volatiles (% by weight) : N/Av

: N/Av

: N/Av

Flash point : 325°F / 163°C

Flash point Method : PMCC Auto-ignition temperature : 532°F / 278°C

Lower flammable limit (% by vol.)

Upper flammable limit (% by vol.) : N/Av

Solubility in water

Flame Projection Length : N/Ap Flashback observed : N/Ap

# Section 10: Stability And Reactivity

Stability and reactivity : Stable if handled below 131oF / 55oC. At higher temperatures decomposition may

take place, and the released heat from decomposition can raise the temperature further and accelerate decomposition. Malathion can corrode iron, steel, tin plate and

copper. It can be rapidly hydrolysed at pH >7.

Hazardous polymerization : Above 284oF / 140oC Fyfanon will decompose rapidly, significantly increasing the risk

of inducing explosions. Direct local heating such as electric heating or by steam must be avoided. The decomposition is to a considerable extent dependant on time as well as temperature due to self-accelerating exothermic and autocatalytic reactions. The reactions involve rearrangements and polymerisation releasing volatile, malodorous

and inflammable compounds such as dimethyl sulfide.

Conditions to avoid : Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible

substances.

Materials To Avoid And Incompatibility

: Incompatible materials (see Section 7).

Hazardous decomposition products

Storage at too high temperatures may induce formation of the more toxic and synergistic contaminant isomalathion. Refer to Section 5 for additional 'Hazardous combustion products'.

# SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs : Eyes, skin, respiratory system, digestive system, central nervous system.

Page 5 of 7 MSDS Revision Date (dd/mm/yyyy): 16/03/2010

YES YES Routes of exposure : Inhalation: YES Skin Absorption: YES Skin & Eyes: Ingestion:

Toxicological data : Fyfanon:

LC50 Inhalation (rat): > 5.2 mg/L / 4 Hrs

LD50 Oral (rat): 5500 mg/kg LD50 Dermal (rat): > 2000 mg/kg

Carcinogenic status No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

: Not expected to have other reproductive effects. Reproductive effects

Not expected to be a teratogen. Teratogenicity

Not expected to be mutagenic in humans. Mutagenicity

**Epidemiology** Not available. None known. Sensitization to material Synergistic materials Not available.

May cause eye and skin irritation. May cause irritation to upper respiratory system. Irritancy

Cholinesterese inhibitor May cause central nervous system depression. Contains a other important hazards

material which can cause peripheral nervous system damage.

Conditions aggravated by overexposure

: None known.

# **SECTION 12 - ECOLOGICAL INFORMATION**

# **Ecotoxicity**

: This product is an insecticide. Malathion is toxic to birds, fish, aquatic invertebtates, aquatic life stages of amphibians and highly toxic to bees. The toxicity of the active ingredients to wildlife species is measured to be:

Fish - 96-hr LC50, Rainbow Trout (Salmo gairdneri) = 0.18 mg/L; 37-day NOEC: 21

µg/L

Invertebrates - 48-hr EC50, Daphnids (Daphnia magna) = 0.72 mg/L; 21-day NOEC:

 $0.06 \mu g/L$ 

Algae - Green algae (Selenastrum capricornutum) 72-Hr LC50= 4.06 mg/L

Birds - LD50, Bobwhite quail (Colinus virginianus) = 359 mg/kg; 5-day dietary LC50:

3497 mg/kg

degraded rapidly.

LD50, Mallard duck (Anas platyrhynchos) = 1485 mg/kg

Earthworms - 14-day LC50, (Eisenia foetida foetida) = 613 mg/kg soil

Bees - LD50, worker honey-bees, acute oral =  $0.38 \mu g/bee$ .

LD50, worker honey-bees, topical =  $0.27 \mu g/bee$ Mobility

: Under normal conditions, the active ingredient is of medium mobility in soil, but it is

Persistence The active ingredient, Malathion, is readily biodegradable. It undergoes rapid

> degradation in the environment and, without problems, in sewage treatment plants. No adverse effects are observed at concentrations up to 100 mg/L in waste water treatment plants. Degradation occurs both aerobically and anaerobically, and biologically as well as abiologically. Under normal conditions, Malathion is of medium mobility in soil, but is degraded rapidly. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

Do not discharge product unmonitored into the environment.

The bioconcentration factor (BCF) of Malathion is 95 (average for several fish Bioaccumulation potential

species).

### Other Adverse Environmental effects

This product is an insecticide. Malathion is toxic to birds, fish, aquatic invertebtates, aquatic life stages of amphibians and highly toxic to bees. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

# SECTION 13 - DISPOSAL CONSIDERATIONS

**Handling for Disposal** 

: Handle waste according to recommendations in Section 7.

**Methods of Disposal** 

: Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Triple rinse (or equivalent) containers, then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill. Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal

environmental agency for specific rules.

**RCRA** 

If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method.

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label			
49CFR/DOT	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (malathion)	9	III	<b>***</b>			
49CFR/DOT Additional information	None.							
TDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (malathion)	9	III	<b>***</b>			
		I .						

### SECTION 15 - REGULATORY INFORMATION

### **US Federal Information:**

OSHA: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200).

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): See Section 6

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: Malathion

### **US State Right to Know Laws:**

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

#### **International Information:**

This product is a Pest Control Product and is not regulated as a Controlled Product under the Hazardous Products Act (HPA).

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

### **SECTION 16 - OTHER INFORMATION**

 HMIS Rating
 \*- Chronic hazard
 0 - Minimal
 1 - Slight
 2 - Moderate
 3 - Serious
 4 - Severe

 Health:
 \*1
 Flammability:
 1
 Reactivity:
 1

Legend : ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

Inh: Inhalation N/Ap: not applicable N/Av: not available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OEHHA - Office of Environmental Health Hazard Assessment OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit PMCC - Pensky Martins Closed Cup

RCRA: Resource Conservation and Recovery Act RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments & Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TPQ: Threshold Planning Quantity TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System1. ACGIH, Threshold Limit Values and Biological Exposure Indices.2. International Agency for Research on Cancer Monographs.

3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases,

(Chempendium, HSDB, RTECs).

4. Material Safety Data Sheet from manufacturer.

5. US EPA Title III List of Lists.6. California Proposition 65 List.

# Prepared for:

References

Cheminova Inc PO Box 110566

One Park Drive, Suite 150 Research Triangle Park NC 27709 Please direct all enquiries to Cheminova.

### Prepared by:

ICC The Compliance Center Inc.

http://www.thecompliancecenter.com



## DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from Cheminova Inc and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Cheminova Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and Cheminova Inc.

Preparation Date (dd/mm/yyyy)

: 19/08/2003

Reviewed Date (dd/mm/yyyy)

: 16/03/2010

Revision No. : 3

Revision Information : (M)SDS sections updated: All

END OF DOCUMENT