GT-180 Instructions

Thank you for choosing the GT-180 System.

The GT-180 system is an effective, and clean method of flying insect control. There are no exploding insect parts, because the unit does not electrocute the insects. It utilizes a unique balance of the ultraviolet light as as attractant to lure flying insects to the adhesive board. GT-180 operates silently and continuously, 24 hours per day. The insects are captured and contained on the adhesive board for easy disposal. Note: The adhesive board should be changed as least once a month.

To achieve optimal results from the GT-180 system, please read these instructions!

A Silent, Insect Control System is an important overall pest management program.


INSTALLATION

The following steps are a guideline to ensure proper installation:

- Step 1.) Find location or source of insect problem, such as trash receptacles or compactors. For optimal results, install the unit below eye level.
- Step 2.) For mounting; locate solid wall structure for placement of unit.
 - Note: GT-180 must be placed 5' away from open food prep areas. Units should be mounted lower than eye level.
- Step 3.) Mark and drill pilot holes & affix mounting screws to match key slots on back of unit.
- Step 4.) Mount the GT-180 unit onto the wall by aligning the key slots to screws.
- Step 5.) Install the adhesive boards into unit.

GROUNDING INSTRUCTIONS

1.) The product is equipped with an appropriate 3-conductor cord and a 3-prong grounding type plug to fit the proper grounding type receptacle. To reduce the risk of an electric shock, the plug must be plugged into an appropriate outlet that is properly installed and grounded:



Consult a qualified electrician or serviceman if the grounding instructions are not completely understood, or if doubt as to whether proper grounding exists.

2.) Extension Cords

Use only a 3-wire extension cords which have 3-prong grounding type plugs and 3-pole receptacles which accept the product's plug. Replace or repair damaged cords.

OPERATING INSTRUCTIONS

- 1.) Plug GT-180 into a standard 110V outlet with ground pin.
- 2.) Insect lamp will light automatically.

For Household and Commercial use only

USER-MAINTENANCE INSTRUCTIONS

- 1.) Replace ultraviolet lamps on an annual basis.
- 2.) Replace glueboard on a regular basis.
- 3.) Clean GT-180 regularly.
- 4.) To remove insects disconnect power, remove the glueboards and discard the contents, replace with new glueboard, reconnect power.
- 5.) To replace lamp disconnect power, remove old tube, replace with new tube, re-connect power. Dispose of old lamps in accordance with disposal laws; see www.lamprecycle.org

WARNING - When using electric appliances, basic precautions should always be followed

INSTRUCTIONS PERTAINING TO A RISK OF FIRE, ELECTRIC SHOCK OR INJURY TO PERSONS

IMPORTANT SAFETY INSTRUCTIONS

WARNING - When using electric appliances, basic precautions should always be followed.

THE GT-180 SYSTEM IS INTENDED FOR INDOOR HOUSEHOLD AND COMMERCIAL USE ONLY.

- 1. Read all instructions before using the appliance
- 2. Do not use outdoors
- 3. Do not unplug by pulling on cord. To unplug, grasp the plug, not the cord.
- 4. Unplug from outlet when not in use and before servicing or cleaning.
- 5. To reduce the risk of electrical shock or fire, do not put GT-180 in water or other liquid. Do not place or store GT-180 where it can fall or be pulled into a tub or sink.
- 6. Always unplug before replacing lamp Replace bulb with same type rated 15 watts.
- 7. All other servicing of units should be performed by an authorized service representative.
- 8. Connect to a properly grounded outlet only. See grounding instruction.

SAVE THESE INSTRUCTIONS